

LOC I-PTW

108.3

APP CRS

276°

Rwy Idg

3181

TDZE

308

Apt Elev

308

LOC RWY 28

HERITAGE FLD (PTW)


▼

⚠

Circling NA south of Rwy 10-28. When local altimeter setting not received, use Wings Fld altimeter setting and increase all MDA 40 feet. Rwy 28 helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH: Climb to 900 on heading 276° then climbing right turn to 2000 on heading 090° and ETX VOR/DME R-160 to GOOGL Int and hold.

ASOS	PHILADELPHIA APP CON	CLNC DEL	UNICOM
119.425	126.85 263.125	118.55	122.7 (CTAF) 0



900

2000

hdg 276°

hdg 090°

ETX R-160

GOOGL INT

GOOGL INT

One Minute Holding Pattern

276°

096°

2000

3 23°

TCH 45

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 45).

4.8 NM

CATEGORY	A	B	C	D
S-28	820-1	512 (600-1)	NA	
CIRCLING	940-1	632 (700-1)	NA	

ELEV 308

TDZE 308

MIRL Rwy 10-28 0
REIL Rws 10 and 28

FAF to MAP 4.8 NM

Knots	60	90	120	150	180
Min:Sec	4:48	3:12	2:24	1:55	1:36

NE-4, 30 OCT 2025 to 27 NOV 2025

NE-4, 30 OCT 2025 to 27 NOV 2025