

## MAYNR THREE DEPARTURE (RNAV)

**TOP ALTITUDE:  
ASSIGNED BY ATC**



RNAV 1 - DME/DME/IRU or GPS.

From SLIPT to MAXIM: RNAV 1 - GPS.

From SLIPT to CANOA: RNAV 1 - GPS.

RADAR required for non-GPS equipped aircraft.

RADAR required.

## TAKEOFF MINIMUMS

Rwy 9L: Standard with minimum climb of 500'/NM to 1300.

Rwy 9R: Standard with minimum climb of 500'/NM to 1500.

Rwy 13: Standard with minimum climb of 500'/NM to 1800.

Rwy 27L: Standard with minimum climb of 500'/NM to 1900.

Rwy 27R: Standard with minimum climb of 500'/NM to 1700.

Rwy 31: Standard with minimum climb of 500' / NM to 1400.

NOTE: Jet aircraft only.

NOTE: Accelerate to 250K until leaving 10000, if unable, advise ATC.

MSA TMB 25 NM

291

MIAMI DEP CON

125.5 354.1

# ATIS

124.0

CLINC DEI

133.0

GND CON

121.7

MIAMI EXEC TOWER★

118.9 (CTAF)

NOTE: Chart not to scale.

(CONTINUED ON FOLLOWING PAGE)

SE-3, 30 OCT 2025 to 27 NOV 2025

MAYNR THREE DEPARTURE (RNAV)

(MAYNR3.MAYNR) 31OCT24

MIAMI, FLORIDA  
MIAMI EXEC (TMB)

SE-3, 30 OCT 2025 to 27 NOV 2025