

WAAS
CH **90325**
W20A

APP CRS
196°

Rwy Idg
TDZE
Apt Elev

5500
662
666

RNAV (GPS) RWY 20

ROCK HILL/YORK COUNTY/BRYANT FLD (UZA)


RNP APCH-GPS.

T

For uncompensated Baro-VNAV systems, procedure NA below -16°C or above 39°C.
When local altimeter setting not received, use Charlotte/Douglas Intl altimeter setting and increase LPV DA to 957 feet, LNAV/VNAV DA to 1084 feet, and all MDAs 60 feet; increase LPV visibility all Cats ½ SM, LNAV/VNAV visibility all Cats ¼ SM, and LNAV visibility Cat C/D ¼ SM. VDP and Baro-VNAV NA when using Charlotte/Douglas Intl altimeter setting. Rwy 20 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:
Climb to 3000 direct CONEL and hold.

ASOS 120.775	CHARLOTTE APP CON 120.05 307.8	GCO 121.725	UNICOM 123.05 (CTAF) 0
------------------------	--	-----------------------	----------------------------------



ELEV 666

TDZE 662

MISSED APCH FIX

CONEL

3000

CONEL

196°

20

5500 X 100

AS

2

MIRL Rwy 2-20 0

*LNAV only.

RW20

TIPDY 2300

CESOX 2300

GP 3.00° TCH 40

1.1 NM

3.9 NM

6.8 NM

CATEGORY	A	B	C	D
LPV DA	912-¾	250 (300-¾)		
LNAV/VNAV DA	1039-1	377 (400-1)		
LNAV MDA	1060-1 398 (400-1)	1060-1 398 (400-1)	1060-1 398 (400-1)	1060-1 398 (400-1)
CIRCLING	1140-1 474 (500-1)	1160-1 494 (500-1)	1340-2 674 (700-2)	1340-2 674 (700-2)