

|                                        |                        |                                                     |
|----------------------------------------|------------------------|-----------------------------------------------------|
| WAAS<br>CH <b>69423</b><br><b>W28A</b> | APP CRS<br><b>284°</b> | Rwy Ldg<br>TDZE <b>1189</b><br>Apt Elev <b>1191</b> |
|----------------------------------------|------------------------|-----------------------------------------------------|

RNAV (GPS) RWY 28

KNOX COUNTY (4I3)

RNP APCH.  
▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 36°C.

MISSED APPROACH: Climb to 3000 direct BONIF and hold.

AWOS-3PT  
**126.05**

COLUMBUS APP CON  
**125.95 317.775**

CLNC DEL  
**119.45**

UNICOM  
**123.05 (CTAF) 0**

MISSED APCH FIX

BONIF

104°

284°

4 NM

MSA RW 28 25 NM

3100

1273±

RW28

SLAPT

1.7 NM to RW28

(FAF) WEBUB

2700

284°

(6.9)

104°

284°

4 NM

HOLD

6000

2800

(IF/IAF) PATIE

2800 NoPT

014°

(9.8)

(IAF) TUCUG

2800 NoPT

305°

(13.6)

(IAF) ROSCO

Procedure NA for arrival on APE VORTAC airway radials 055 CW 168.

APPLETON APE

3000

099°

(13.5)

ELEV 1191

TDZE 1189

10

5504 X 100

28

284°

3000

BONIF

\*LNAV only

SLAPT

1.7 NM to RW28

\*1 NM to RW28

RW28

WEBUB

2700

PATIE

4 NM Holding Pattern

104°

284°

6000

2800

GP 3.00°

TCH 40°

\*1760

2700

1 NM

0.7

2.9 NM

6.9 NM

| CATEGORY     | A | B      | C           | D |
|--------------|---|--------|-------------|---|
| LPV DA       |   | 1389-1 | 200 (200-1) |   |
| LNAV/VNAV DA |   | 1439-1 | 250 (300-1) |   |
| LNAV MDA     |   | 1540-1 | 351 (400-1) |   |

MIRL Rwy 10-28 0

REIL Rwys 10 and 28 0

MOUNT VERNON, OHIO

AL-5447 (FAA)

25275

MOUNT VERNON, OHIO

AL-5447 (FAA)

25275

40°20'N-82°32'W

RNAV (GPS) RWY 28