


WAAS CH 73041 W26A	APP CRS 260°	Rwy Ldg TDZE 46 Apt Elev 49	5900
--	------------------------	---	-------------

RNAV (GPS) RWY 26

WILEY POST-WILL ROGERS MEML (BRW)(PABR)

RNP APCH - GPS.	MISSED APPROACH: Climb to 2000 direct OBCIN and hold.
▼ ▲ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C or above 54°C. Circling NA for Cat A north of Rwy 8-26	

AFIS 132.15	ANCHORAGE CENTER 135.3 239.25	BARROW RADIO 123.6 (CTAF) 0
-----------------------	---	---------------------------------------



ELEV 49	D	TDZE 46
----------------	----------	----------------

2000 OBCIN SEKTY 3.5 NM to RW26 ZUMTU 1700 ASUKY 4 NM Holding Pattern 0.9 NM to RW26 RW26 260° 1200 1700 2000 4000 GP 3.00° TCH 50				
CATEGORY	A	B	C	D
LPV DA	246-1 200 (200-1)			
LNAV/VNAV DA	296-1 250 (300-1)			
LNAV MDA	360-1 314 (400-1)			
CIRCLING	420-1 371 (400-1)	500-1 451 (500-1)	500-1½ 451 (500-1½)	680-2 631 (700-2)

REIL Rwy 26 0
HIRL Rwy 8-26 0