

WAAS

CH 82606

W36A

APP CRS

005°

Rwy Ldg

12600

TDZE

616

Apt Elev

629

RNAV (GPS) RWY 36L

HUNTSVILLE INTL-CARL T JONES FLD (HSV)

RNP APCH-GPS.

ASR

7

▲

Circling NA for Cats C/D/E east of Rwy 18L-36R. Simultaneous approach authorized. LNAV procedure NA during simultaneous operations. Use of FD or AP required during simultaneous operations. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -8°C or above 54°C. For inop ALS, increase LPV Cat E visibility to RVR 4000, LNAV/VNAV all Cats visibility to RVR 4500, and LNAV Cat E visibility to RVR 6000.

MALSR

7

▲

AS

7

▲

MISSED APPROACH:

Climb to 3000 direct HAGUR and hold.

ATIS	HUNTSVILLE APP CON *	HUNTSVILLE TOWER *	GND CON	CLNC DEL	UNICOM
121.25	125.6 354.1	127.6 (CTAF) 350.35	121.9 269.525	120.35	122.95

CAUTION: Numerous migratory bird flocks in area. Wildlife Refuge Area south of airport.

7 NM Holding Pattern		BOSAC		CECAB		HEREG 2.6 NM to RWY36L		3000 HAGUR				
5000 ← 185°		3100 → 005°		2400		1480		RWY36L				
GP 3.00°		TCH 53		7.1 NM		2.9 NM		1.5 NM				
CATEGORY	A	B	C	D	E							
LPV DA	816/18					200 (200-½)						
LNAV/VNAV DA	892/24					276 (300-½)						
LNAV MDA	1000/24	384 (400-½)	1000/35			384 (400-¾)						
CIRCLING	1160-1	531 (600-1)	1160-1½	1240-2	1260-2¼	531 (600-1½)	611 (700-2)	631 (700-2¼)				

ELEV 629

TDZE 616

TDZ/CL Rwy 18R and 36L

HIRL Rwy 18L-36R and 18R-36L

HUNTSVILLE, ALABAMA

Amdt 3 27JAN22

HUNTSVILLE INTL-CARL T JONES FLD (HSV)

34°38'N-86°47'W

RNAV (GPS) RWY 36L