

WAAS CH 99436 W35A	APP CRS 354°	Rwy Idg 5506 TDZE 1155 Apt Elev 1160
--	------------------------	---

RNAV (GPS) RWY 35
STROTHER FLD (WLD)

RNP APCH.

▼ Baro-VNAV and VDP NA when using Wichita Dwight D Eisenhower NH altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -1.5°C or above 54°C. When local altimeter setting not received, use Wichita Dwight D Eisenhower NH altimeter setting: increase LPV DA to 1509 feet and all visibilities $\frac{1}{4}$ SM; increase LNAV/VNAV DA to 1557 feet and all visibilities $\frac{1}{4}$ SM; increase all MDA 120 feet, LNAV Cat C visibility $\frac{3}{8}$ SM and Circling Cat C visibility $\frac{1}{4}$ SM.

MISSED APPROACH:
Climb to 3600 direct
ECUWO and hold.

ASOS 118.025	KANSAS CITY CENTER 127.8 319.1	UNICOM 122.8 (CTAF) 0
------------------------	--	--


MISSED APCH FIX

4 NM

174°

354°

ECUWO

[illegible]

CATEGORY		A	B	C	D
LPV	DA	1405-3/4 250 (300-3/4)			NA
LNAV/ VNAV	DA	1453-1 298 (300-1)			NA
LNAV	MDA	1640-1 485 (500-1)	1640-1 3/8 485 (500-1 3/8)		NA
 CIRCLING		1680-1 520 (600-1)	1680-1 1/2 520 (600-1 1/2)		NA

