



LOC/DME I-TXH 110.7 Chan 44	APP CRS 350°	Rwy Idg TDZE 78 Apt Elev 82
---	------------------------	---

ILS or LOC RWY 35
SUGAR LAND RGNL (SGR)

DME required. RADAR required for procedure entry.	MISSED APPROACH: Climb to 900 then climbing left turn to 2000 on I-TXH localizer south course to HULLO/I-TXH 6.3 DME and hold.
VDP NA when using William P Hobby altimeter setting. When local altimeter setting not received, use William P Hobby altimeter setting and increase all DA 51 feet and all MDA 60 feet and S-LOC 35 Cat C/D visibility 1/8 mile, and Circling Cat C/D visibility 1/4 mile.	

ATIS 118.125	HOUSTON APP CON 123.8 257.7	SUGAR LAND TOWER* 118.65 (CTAF) 0	GND CON 121.4	CLNC DEL 121.4	CLNC DEL 119.25 (when twr closed)	UNICOM 122.95
------------------------	---------------------------------------	--	-------------------------	--------------------------	--	-------------------------



900	2000	HULLO I-TXH 6.3	*600 when using William P Hobby altimeter setting.			
*LOC only.	I-TXH 5 crs	I-TXH 1.9	I-TXH 1.1	I-TXH 2.6	I-TXH 6.3	Remain within 10 NM
*540		1800	1800	2200	350°	GS 3.00° TCH 56
0.9 NM		0.7 NM	3.7 NM			
CATEGORY	A	B	C	D		
S-ILS 35	278-3/4		200 (200-3/4)			
S-LOC 35	400-1		322 (400-1)			
CIRCLING	720-1		638 (700-1)		720-1 3/4	720-2
					638 (700-1 3/4)	638 (700-2)