

APP CRS	Rwy Idg
076°	4002
	TDZE
	1228
	Apt Elev
	1228

RNAV (GPS) RWY 8

ROSTRAVER (FWQ)

▼


▲

NA

When VGSi inop, Straight-in/Circling Rwy 8 procedure NA at night. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Allegheny County altimeter setting and increase all MDA 40 feet; increase LNAV Cats C/D visibility 1/8 mile. Rwy 8 helicopter visibility reduction below 1 SM NA. Rwy 26 helicopter visibility reduction below 3/4 SM NA.

MISSED APPROACH:
Climb to 3700 direct
FURIX and hold.

AWOS-3	PITTSBURGH APP CON	UNICOM
118.475	119.35 337.4	122.8 (CTAF) 0



ELEV 1228

TDZE 1228

3700

FURIX

▲

EROCU

EYOPO

RW08

3000

076°

3000

3.00°

TCH 51

6 NM

5.4 NM

CATEGORY	A	B	C	D
LNAV MDA	1720-1	492 (500-1)	1720-1 3/8	492 (500-1 3/8)
CIRCLING	1720-1	1760-1	1760-1 1/2	1920-2 1/4
	492 (500-1)	532 (600-1)	532 (600-1 1/2)	692 (700-2 1/4)

MIRL Rwy 8-26 0

REIL Rwys 8 and 26 0