

WAAS
CH **72704**
W13A

APP CRS
128°

Rwy Idg **4300**
TDZE **896**
Apt Elev **900**

RNAV (GPS) RWY 13

CROOKSTON MUNI/KIRKWOOD FLD (CKN)

RNP APCH


▼ Baro-VNAV NA when using Grand Forks altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). When local altimeter setting not received, use Grand Forks altimeter setting and increase LPV DA to 1208 feet and LNAV/VNAV DA to 1272 feet; increase all MDA's 80 feet and Circling Cat C visibility ¼ SM. Circling Rwy's 6, 24, 17, 35 NA at night.

MISSED APPROACH: Climb to 3000 direct FAPVU and hold.

AWOS-3
126.425

GRAND FORKS APP CON ★
118.1 318.1

UNICOM
122.7 (CTAF) ①



ELEV 900

TDZE 896

128° to RW13

3

2096 X 200

0.4% UP

2977 X 200

4300 X 75

35

51

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 30).

5 NM Holding Pattern

3000

308°

128°

128°

BEDSE

2600

RW13

GP 3.00° TCH 40

6.5 NM

5.2 NM

CATEGORY	A	B	C	D
LPV DA	1146-1	250 (300-1)		NA
LNAV/VNAV DA	1210-1	314 (400-1)		NA
LNAV MDA	1360-1	464 (500-1)	1360-1¼ 464 (500-1¼)	NA
CIRCLING	1360-1	460 (500-1)	1480-1½ 580 (600-1½)	NA

REIL Rwy's 13 and 31 ①
MIRL Rwy 13-31 ①

NC-1, 30 OCT 2025 to 27 NOV 2025

NC-1, 30 OCT 2025 to 27 NOV 2025