

WAAS CH 99306 W32A	APP CRS 316°	Rwy Idg TDZE 323 Apt Elev 327
--	------------------------	---

RNAV (GPS) RWY 32

EAST GEORGIA RGNL (SBO)

▼


Baro-VNAV and VDP NA when using Vidalia altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below +15°C (5°F) or above 54°C (130°F).

▲

When local altimeter setting not received, use Vidalia altimeter setting and increase all DA to 638 feet and all MDA 80 feet; increase LNAV C/D visibility ¼ SM, and Circling C/D visibility ¼ SM. DME/DME RNP-0.3 NA. Rwy 32 helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH: Climb to 800 then climbing left turn to 2500 direct WINSI and hold.

AWOS-3 133.375	ATLANTA CENTER 127.95 343.75	UNICOM 122.975 (CTAF) 1
--------------------------	--	-----------------------------------



ELEV 327

TDZE 323

800

2500

WINSI

*LNAV only.

WINSI

4 NM Holding Pattern

RW32

JIDIK 2000

WINSI

2000

2500

136°

316°

136°

GP 3.00° TCH 57

1.3

3.8 NM

6.9 NM

CATEGORY	A	B	C	D
LPV DA		573-1	250 (300-1)	
LNAV/ VNAV DA		573-1	250 (300-1)	
LNAV MDA	780-1	457 (500-1)	780-1½	457 (500-1½)
CIRCLING	900-1 573 (600-1)	920-1 593 (600-1)	1000-2 673 (700-2)	1000-2¼ 673 (700-2¼)