

LOC/DME I-PKQ 110.3 Chan 40	APP CRS 356°	Rwy Ldg 35C 35L TDZE 13400 13400 563 564 Apt Elev 607 607	ILS or LOC RWY 35C DALLAS-FORT WORTH INTL (DFW)
--	------------------------	--	--

Inoperative table does not apply to Sidestep Rwy 35L Cats A and B.
DME or RADAR required.
Simultaneous approach authorized with Rwy 35R, Rwy 36L/R.

Rwy 35C
ALSF-2

Rwy 35L
MALSR

MISSED APPROACH: Climb to 3000 on TTT VOR/DME R-356 to BOSSI/TTT 19.7 DME/RADAR and hold.

D-ATIS ARR 123.775 DEP 135.925	LONE STAR APP CON 127.075	DFW TOWER 126.55 127.5 EAST 124.15 134.9 WEST	GND CON 121.65 121.8 EAST 121.85 WEST	CLNC DEL 128.25	CPDLC
--	-------------------------------------	---	---	---------------------------	-------

RADAR REQUIRED

MAVERICK
113.1 TTT
Chan 78

JOBBS INT
I-PKQ 4.5
RADAR

DAYZZ
I-PKQ 7.5
RADAR

TUFFO
I-PKQ 13.8
RADAR

RAYMA
I-PKQ 16.9
RADAR

LOCALIZER 110.3
I-PKQ
Chan 40

COWBOY
116.2 CVE
Chan 109

MSA TTT 25 NM
2700
090°
270°
3600

ALTERNATE MISSED
APCH FIX

GRABE
FUZ 35.4

115.7 FUZ
R-012
Chan 104

114.6 BYP
Chan 93

BOSSI
TTT R-356

VGSI and ILS glidepath not coincident
(VGSI Angle 3.00/TCH 76).

RAYMA
I-PKQ 16.9
RADAR

TUFFO
I-PKQ 13.8
RADAR

DAYZZ
I-PKQ 7.5
RADAR

JOBBS INT
I-PKQ 4.5
RADAR

3000

BOSSI

TTT R-356

* LOC only

356°

5000

6000

GS 3.00°
TCH 59

0.1 NM

3.5 NM

3 NM

6.3 NM

3.2 NM

CATEGORY

A

B

C

D

S-ILS 35C

763/18

200 (200-½)

S-LOC 35C

1000/24

437 (400-½)

1000/40

437 (400-¾)

SIDESTEP 35L

1000/55

436 (400-1)

1000-1½

436 (400-1½)

FAF to MAP 4.6 NM

Knots 60 90 120 150 180

Min:Sec 4:36 3:04 2:18 1:50 1:32

DALLAS-FORT WORTH, TEXAS

Amcl 3 18SEP14

32°54'N-97°02'W

DALLAS-FORT WORTH INTL (DFW)

ILS or LOC RWY 35C