V


BLOKR SEVEN DEPARTURE (RNAV)

CHICAGO DEP CON
119.35 354.075
D-ATIS
126.675
GND CON

RNAV 1 - DME/DME/IRU or GPS.
RADAR required. RADAR required for non-GPS equipped aircraft.

CHICAGO/ROMEOVILLE, ILLINOIS

TOP ALTITUDE: ,---1300



1180

BACEN

BLOKR

27 NOV 2025

2

30 OCT 2025

EC-3,

TAKEOFF MINIMUMS:


120.425

LEWIS TOWER ★ 134.8 (CTAF)

- Rwy 2: Standard with minimum climb of 420' per NM to 2700.
- Rwy 9: Standard with minimum climb of 310' per NM to 2700. Rwy 20: Standard with minimum climb of 370' per NM to 2700.
- Rwy 27: Standard with minimum climb of 340' per NM to 2700.

NOTE: Turbojet departures maintain 250K until advised by ATC.

NOTE: ROBERTS Transition: For aircraft inbound to CMI or STL, or as assigned by ATC.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF RUNWAY 2: Climb on heading 015° to 1300, then as assigned by ATC, for vectors to BACEN, thence. . . .


TAKEOFF RUNWAY 9: Climb on heading 089° to 1180, then as assigned by ATC, for vectors to BACEN, thence. . . .

TAKEOFF RUNWAY 20: Climb on heading 195° to 1180, then as assigned by ATC, for vectors to BACEN, thence. . . .

TAKEOFF RUNWAY 27: Climb on heading 269° to 1180, then as assigned by ATC, for vectors to BACEN, thence. . . .

. . . . on track 195° to BLOKR, then on (transition). Maintain 3000. Expect filed altitude 10 minutes after departure.

BEKKI TRANSITION (BLOKR7.BEKKI): ROBERTS TRANSITION (BLOKR7.RBS):



BLOKR SEVEN DEPARTURE (RNAV) (BLOKR7.BLOKR) 310CT24

CHICAGO/ROMEOVILLE, ILLINOIS LEWIS UNIVERSITY (LOT)