

WAAS
CH **56221**
W33A

APP CRS
331°

Rwy Idg
TDZE
Apt Elev
5500
217
236

RNAV (GPS) RWY 33

RICHMOND EXEC/CHESTERFIELD COUNTY (F'CI)

▼

▲ NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C (5°F) or above 54°C (130°F). When local altimeter setting not received, use Richmond Intl altimeter setting; increase LPV DA to 546 feet and all visibilities ½ SM; increase LNAV/VNAV DA to 634 feet and all visibilities ½ SM; increase all MDAs 40 feet and LNAV visibility Cat C/D ½ SM and Circling visibility Cat D ½ SM. DME/DME RNP-0.3 NA. For inop MALSR, increase LPV all Cats visibility to 1 mile and LNAV Cat C/D to 1½ mile. For inop MALSR when using Richmond Intl altimeter setting, increase LPV all Cats visibility to 1 ½ mile. Baro-VNAV and VDP NA when using Richmond Intl altimeter setting.

MALSR

MISSED APPROACH:
Climb to 3000 direct
DOCEV and hold.

AWOS-3PT
128.625

POTOMAC APP CON
126.75 307.2

CLNC DEL
124.6

UNICOM
123.05 (CTAF) 0

