

|                                        |                        |                                                               |
|----------------------------------------|------------------------|---------------------------------------------------------------|
| WAAS<br>CH <b>93900</b><br><b>W35A</b> | APP CRS<br><b>353°</b> | Rwy Idg <b>5364</b><br>TDZE <b>650</b><br>Apt Elev <b>658</b> |
|----------------------------------------|------------------------|---------------------------------------------------------------|

# RNAV (GPS) RWY 35

## NEW BRAUNFELS NTL (BAZ)

RNP APCH.

**⚠** When local altimeter setting not received, use San Marcos Rgnl altimeter setting; increase LPV DA to 972 feet, LNAV/VNAV DA to 1153 feet; increase all MDAs 60 feet and visibility LNAV Cat C and D ¼ SM. Baro-VNAV and VDP NA when using San Marcos Rgnl altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 47°C (116°F).

**MISSED APPROACH:** Climb to 3100 direct FONEK and via 340° track to BRAUN and hold, continue climb-in-hold to 3100.

|                 |                                       |                                             |                    |                    |                                         |                 |
|-----------------|---------------------------------------|---------------------------------------------|--------------------|--------------------|-----------------------------------------|-----------------|
| ATIS<br>119.325 | SAN ANTONIO APP CON<br>124.45 335.625 | NEW BRAUNFELS TOWER*<br>127.05 (CTAF) 285.4 | GND CON<br>120.175 | CLNC DEL<br>134.75 | CLNC DEL<br>134.75<br>(When twr closed) | UNICOM<br>122.7 |
|-----------------|---------------------------------------|---------------------------------------------|--------------------|--------------------|-----------------------------------------|-----------------|