

WAAS
CH **45905**
W22A

APP CRS
215°

Rwy Ldg **7193**
TDZE **26**
Apt Elev **26**

RNAV (GPS) RWY 22

PUNTA GORDA (PGD)

▼

Baro-VNAV NA when using Page Fld altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 1°C or above 54°C. When local altimeter setting not received, use Page Fld altimeter setting and increase LPV DA to 276, LNAV/VNAV DA to 360, and all MDAs 60 feet; increase LNAV Cats C and D visibility ¼ SM, and Circling Cats C and D visibility ¼ SM.

▲

MISSED APPROACH: Climb to 2000 direct BULOW and hold.

RNP APCH.

ATIS 135,675	FORT MYERS APP CON★ 127.05 306.2	PUNTA GORDA TOWER★ 121.0 (CTAF) 0	GND CON 119.55	UNICOM 122,975
------------------------	--	---	--------------------------	--------------------------

Procedure NA for arrivals at ROGAN on V7 northbound.

Procedure NA for arrivals at QUNCY on V521 southbound.

MISSED APCH FIX BULOW

GP 3.00° TCH 40

CATEGORY	A	B	C	D
LPV DA	226-3/4	200 (200-3/4)		
LNAV/VNAV DA	310-1	284 (300-1)		
LNAV MDA	420-1	394 (400-1)	420-1 1/8	394 (400-1 1/8)
CIRCLING	460-1 434 (500-1)	580-1 554 (600-1)	600-1 1/2 574 (600-1 1/2)	740-2 1/4 714 (800-2 1/4)

ELEV 26

D

TDZE 26

215°

27

2636 X 60

5286 X 130

7193 X 150

33

4

TWR

HIRL Rwy 4-22

MIRL Rwy 15-33

REIL Rws 4, 15, 22 and 33

2000

BULOW

VGSI and descent angles not coincident (VGSI Angle 3.00/TCH 31).

*LNAV only.

EGOTE 1.5 NM to RW22

DOGLE 1600

AIRVA 2000

540*

1600

GP 3.00° TCH 40

CATEGORY	A	B	C	D
LPV DA	226-3/4	200 (200-3/4)		
LNAV/VNAV DA	310-1	284 (300-1)		
LNAV MDA	420-1	394 (400-1)	420-1 1/8	394 (400-1 1/8)
CIRCLING	460-1 434 (500-1)	580-1 554 (600-1)	600-1 1/2 574 (600-1 1/2)	740-2 1/4 714 (800-2 1/4)

PUNTA GORDA, FLORIDA

Amdt 2A 30JAN20

26°55'N-81°59'W

PUNTA GORDA (PGD)

RNAV (GPS) RWY 22