

APP CRS
280°

Rwly Idg
TDZE
Apt Elev

3803
422
424

RNAV (GPS) RWY 28

WILLIAMSON/SODUS (SDC)

RNP APCH - GPS.

Procedure NA at night. Rwy 28 helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use Rochester altimeter setting and increase all MDAs 80 feet and LNAV visibility Cat C ½ SM, and Circling visibility Cat C ¼ SM.

MISSED APPROACH:
Climb to 3000 direct GOYER and hold.

AWOS-3
124.2

ROCHESTER APP CON
119.55 269.6

UNICOM
122.8 (CTAF) 0

The main chart displays the RNAV (GPS) RWY 28 approach. Key features include:

- Obstacles:** A 764' obstacle near RWY 28, a 735 ±' obstacle, and a 929' obstacle.
- Altitudes:** 3100' and 3200' MSL altitudes for various segments.
- Navigation:** 30 NM to ZIKEM, 30 NM to JORAX, and 30 NM to WALCO (NoPT) segments.
- Waypoints:** GOYER, ZIKEM, JORAX, WALCO, and JAKRR.
- Angles:** 101°, 191°, 281°, and 280° headings.
- Distances:** 4 NM, 6 NM, and 12 NM segments.

ELEV 424 TDZE 422

3000 GOYER

3803 x 60

28°

3000

GOYER

3.20°

TCH 43

280°

281°

2000

281°

4.5 NM

6 NM

WALCO

4 NM Holding Pattern

101°

281°

6000

3100

CATEGORY	A	B	C	D
LNAV MDA	980-1	558 (600-1)	980-1½ 558 (600-1½)	NA
CIRCLING	1000-1 576 (600-1)	1020-1 596 (600-1)	1120-2 696 (700-2)	NA

WILLIAMSON/SODUS, NEW YORK

Amdbt 2B 06OCT22

43°14'N-77°07'W

WILLIAMSON/SODUS (SDC)

RNAV (GPS) RWY 28