

WAAS
CH **49131**
W17A

APP CRS
166°

Rwy Idg **4010**
TDZE **1522**
Apt Elev **1523**

RNAV (GPS) RWY 17
LANGLADE COUNTY (AIG)

RNP APCH - GPS.

Baro-VNAV NA when using AUW altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. Procedure NA at night. Helicopter visibility reduction below 1 SM NA. When local altimeter setting not received, use AUW altimeter setting and increase LPV DA to 1877 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 2029 feet and all visibilities ¼ SM. Increase all MDAs 120 feet and LNAV visibility Cat C/D ¼ SM, and Circling visibility Cat C/D ½ SM.

MISSED APPROACH:
Climb to 3300 direct ZABVI and hold.

AWOS-3 119.075	MINNEAPOLIS CENTER 124.4 317.7	UNICOM 122.8 (CTAF) 1
--------------------------	--	---------------------------------

CATEGORY	A	B	C	D
LPV DA	1772-1		250 (300-1)	
LNAV/VNAV DA	1924-1⅓		402 (400-1⅓)	
LNAV MDA	1920-1 398 (400-1)		1920-1⅓ 398 (400-1⅓)	
CIRCLING	2120-1 597 (600-1)		2260-2 737 (800-2) 2260-2¼ 737 (800-2¼)	

ANTIGO, WISCONSIN
Amdt 2B 26DEC24

45°09'N-89°07'W

LANGLADE COUNTY (AIG)
RNAV (GPS) RWY 17