

WAAS CH 42830 W21A	APP CRS 213°	Rwy Idg TDZE 1007 Apt Elev 1019	5000 1007 1019
--	------------------------	---	---

RNAV (GPS) RWY 21

MOUNT STERLING/MONTGOMERY COUNTY (IOB)

RNP APCH - GPS


▼

NA

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use Lexington altimeter setting and increase LPV DA to 1332 feet and all visibilities ¼ SM. Increase LNAV/VNAV DA to 1555 feet and all visibilities ¼ SM. Increase all MDAs 80 feet and LNAV visibility Cat C/D ½ SM, and Circling visibility Cat C/D ¼ SM. Baro-VNAV and VDP NA when using Lexington altimeter setting. Rwy 21 helicopter visibility reduction below ¼ SM NA.

MISSED APPROACH:
Climb to 3000 direct COXIT and hold.

AWOS-3 120.675	LEXINGTON APP CON 120.15 259.3	GCO 121.72	CTAF 122.8
--------------------------	--	----------------------	----------------------



ELEV 1019		TDZE 1007	
MISSED APCH FIX COXIT		VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 40).	
*LNAV only.		4 NM Holding Pattern	
RW21		GP 3.00° TCH 57	
CATEGORY			
LPV DA		1257-¾ 250 (300-¾)	
LNAV/VNAV DA		1480-1½ 473 (500-1½)	
LNAV MDA		1460-1 453 (500-1) 1460-1½ 453 (500-1½)	
CIRCLING		1540-1 521 (600-1) 1560-1 541 (600-1) 1740-2 721 (800-2) 1740-2¼ 721 (800-2¼)	