


WAAS CH 93936 W16A	APP CRS 160°	Rwy Idg TDZE 1257 Apt Elev 1266	5000 1257 1266
--	------------------------	---	---

RNAV (GPS) RWY 16
GWINNER/ROGER MELROE FLD (GWR)


⚠ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C (2°F) or above 47°C (117°F). DME/DME RNP-0.3 NA. Circling NA to Rwys 6 and 24. Baro-VNAV and VDP NA when using Fargo altimeter setting. When local altimeter setting not received, use Fargo altimeter setting: increase LPV DA to 1683 feet and visibility ¾ SM, and LNAV/VNAV DA to 1803 feet and visibility ¾ SM; increase all MDAs 180 feet and visibility LNAV Cat C/D ¾ SM, and Circling Cat C ¾ SM, and Circling Cat D ½ SM.

MISSED APPROACH:
Climb to 3500 direct
WASWK and hold.

AWOS-3 118.325	MINNEAPOLIS CENTER 127.35 278.3	UNICOM 122.7 (CTAF) 0
--------------------------	---	---------------------------------



ELEV 1266	TDZE 1257
------------------	------------------



4 NM Holding Pattern				VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 25).				3500	WASWK
3500				JIMOD				ASABE	
GP 3.10°				2900				2.7 NM to	
TCH 40				2900				RW16	
				*2180				*1.2 NM to	
								RW16	
CATEGORY	A	B	C	D					
LPV DA	1507-1				250 (300-1)				
LNAV/VNAV DA	1627-1¼				370 (400-1¼)				
LNAV MDA	1660-1		403 (400-1)	1660-1½		403 (400-1½)			
CIRCLING	1780-1		514 (600-1)	1840-1½		574 (600-1½)	2060-2½		794 (800-2½)