RNAV (GPS) RWY 5

BESSEMER NTL (EKY)

WAAS	APP CRS	Rwy Ldg	6007
CH 65999	053°	TDZE	700
W05A		Apt Elev	700

Baro-VNAV NA when using Alabaster altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C (4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Alabaster altimeter setting and increase LPV DA to 941 feet, LNAV/VNAV DA to 1285 feet, and all MDAs 60 feet; increase Circling Cat D visibility ¼ SM.

MISSED APPROACH: Climb to 4000 direct IKIMY and on track 108° to HANDE and hold.

AWOS-3PT	BIRMINGHAM APP CON	CLNC DEL	UNICOM
118.825	124.9 351.85	123.75	123.0 (CTAF) L





CATEGORY	A	B	C	D
LPV DA	900-¾	200 (200-¾)		
LNAV/VNAV DA	1244-2	544 (600-2)		
LNAV MDA	1160-1	460 (500-1)	1160-1⅜ 460 (500-1⅜)	1160-1½ 460 (500-1½)
CIRCLING	1200-1	500 (500-1)	1220-1½ 520 (600-1½)	1320-2 620 (700-2)



HIRL Rwy 5-23 L
REIL Rwys 5 and 23 L

SE-4, 30 OCT 2025 to 27 NOV 2025
SE-4, 30 OCT 2025 to 27 NOV 2025