

WAAS CH 69212 W25A	APP CRS 252°	Rwy Idg 4703 TDZE 913 Apt Elev 913
--	------------------------	---

RNAV (GPS) RWY 25
FLEMING-MASON (FGX)


RNP APCH - GPS.

A Baro-VNAV and VDP NA when using Blue Grass altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When local altimeter setting not received, use Lexington altimeter setting and increase LPV DA to 1240 feet and all visibilities ¼ SM; increase LNAV/VNAV DA to 1290 feet and all visibilities ¾ SM; increase all MDAs 140 feet and LNAV visibility Cat C/D ¾ SM, and Circling visibility Cat C/D ½ SM.



MISSED APPROACH:
Climb to 3000 direct
DIKRY and hold.

AWOS-3
118.125

INDIANAPOLIS CENTER
124.225 360.725

UNICOM
123.0(CTAF) L

ELEV 913	D	TDZE 913
----------	----------	----------



CATEGORY	A	B	C	D
LPV DA	1113- ³ / ₄ 200 (200- ³ / ₄)			
LNAV/ VNAV DA	1163- ³ / ₄ 250 (300- ³ / ₄)			
LNAV MDA	1260-1 347 (400-1)			
CIRCLING	1320-1 407 (500-1)	1380-1 467 (500-1)	1520-1 ³ / ₄ 607 (700-1 ³ / ₄)	1520-2 607 (700-2)

MIRL Rwy 7-25 **L**

REIL Rwys 7 and 25 L

FLEMINGSBURG, KENTUCKY

Amdt 1 30NOV23

38°32'N-83°45'W

FLEMING-MASON (FGX)

RNAV (GPS) RWY 25

SE-1, 30 OCT 2025 to 27 NOV 2025