

WAAS CH 86935 W01A	APP CRS 009°	Rwy Idg TDZE 499 Apt Elev 499	5007
--	------------------------	---	-------------

RNAV (GPS) RWY 1


WILLIAM L WHITEHURST FLD (M08)

NA


DME/DME RNP-0.3 NA. When local altimeter setting not received, use Jackson altimeter setting and increase all MDA 80 feet, increase LP Cats C/D visibilities ⅜ mile, and LNAV Cats C/D and Circling Cats C/D visibilities ¼ mile. Rwy 1 helicopter visibility reduction below 1 SM NA.

MISSED APPROACH: Climb to 2500 direct HESKA and hold.

AWOS-3 121.125	MEMPHIS CENTER 124.35 318.1	UNICOM 123.0 (CTAF)
--------------------------	---------------------------------------	-------------------------------



4 NM Holding Pattern		Visual Segment - Obstacles.		2500	HESKA
2500		LOHNI	SADJI	JUSES	RW01
189°		009°	009°	189°	
009°		009°	189°	189°	
6.6 NM		2.6 NM	1.4 NM		
CATEGORY	A	B	C	D	
LP MDA	860-1		361 (400-1)		
LNAV MDA	880-1	381 (400-1)	880-1½	381 (400-1½)	
CIRCLING	980-1	481 (500-1)	1100-1¾ 601 (700-1¾)	1360-2¾ 861 (900-2¾)	



SE-1, 30 OCT 2025 to 27 NOV 2025

SE-1, 30 OCT 2025 to 27 NOV 2025