

WAAS
CH 77732
W18A

APP CRS
177°

Rwy Ldg
TDZE 1080
Apt Elev 1088

RNAV (GPS) RWY 18

AMERY MUNI (AHH)

▼

NA

Rwy 18 helicopter visibility reduction below ¾ SM NA. Use New Richmond altimeter setting; when not received, use Osceola altimeter setting and increase all MDAs 20 feet and Circling Cat C visibility ¼ SM.

MISSED APPROACH:
Climb to 3000 direct FISOM and hold.

RNH AWOS-3 120.0	MINNEAPOLIS CENTER 125.3 335.6	UNICOM 122.8 (CTAF) 0
---------------------	-----------------------------------	--------------------------

4 NM Holding Pattern		Visual Segment - Obstacles.		3000 FISOM
CATEGORY	A	B	C	D
LP MDA	1500-1	420 (500-1)	1500-1¼ 420 (500-1¼)	NA
LNAV MDA	1600-1	520 (600-1)	1600-1½ 520 (600-1½)	NA
CIRCLING	1740-1	652 (700-1)	1740-1¾ 652 (700-1¾)	NA

AMERY, WISCONSIN
Amdt 1B 05DEC19

45°17'N-92°23'W

AMERY MUNI (AHH)
RNAV (GPS) RWY 18