



WAAS CH 72921 W17A	APP CRS 174°	Rwy Idg TDZE 994 Apt Elev 1002
--	------------------------	--

RNAV (GPS) RWY 17


PERRY MUNI (F22)

RNP APCH.	Baro-VNAV NA when using KPNC altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. When VGSI inop, procedure NA at night. Rwy 17 helicopter visibility reduction below 1 SM NA. Obtain local altimeter setting on CTAF; when not received, use Ponca City altimeter setting and increase all DA 53 feet, all MDA 60 feet and increase LNAV/VNAV all Cats and LNAV Cat C visibility ¼ mile.	MISSED APPROACH: Climb to 3000 direct HIGY and on track 192° to YUPUD and hold.
-----------	--	---

KANSAS CITY CENTER 127.8 319.1	UNICOM 122.8 (CTAF) 0
-----------------------------------	--------------------------



4 NM Holding Pattern	AHOBY	*LNAV only	3000	HIGY	tr 192°	YUPUD
3000	354°	174°	2600	CUXOP 1.6 NM to RW17	RW17	
GP 3.00° TCH 37	174°	*1520				
	6 NM	3.4 NM	1.6			
CATEGORY	A	B	C	D		
LPV DA	1244-1	250 (300-1)		NA		
LNAV/VNAV DA	1434-1½	440 (500-1½)		NA		
LNAV MDA	1360-1	366 (400-1)	1360-1⅛ 366 (400-1⅛)	NA		



SC-1, 30 OCT 2025 to 27 NOV 2025

SC-1, 30 OCT 2025 to 27 NOV 2025