

APP CRS
292°

Rwy Idg
TDZE
Apt Elev

3600
1607
1607


RNP APCH.

▼
▲ NA

Circling Rwy 11 NA at night. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C (0°F) or above 54°C (130°F). Baro-VNAV NA when using Devil's Lake altimeter setting. When local altimeter setting not received, use Devil's Lake altimeter setting: increase LNAV/VNAV DA to 2246 feet and visibility LNAV/VNAV all Cats ½ SM; increase all MDA 140 feet and visibility LNAV and Circling Cat C ½ SM.

MISSED APPROACH:
Climb to 3400 direct
NUTFO and hold.

AWOS-3 118.825	MINNEAPOLIS CENTER 135.25 256.7	UNICOM 122.8 (CTAF) 0
-------------------	------------------------------------	--------------------------



ELEV 1607 TDZE 1607

3400
NUTFO

VGSI and RNAV glidepath not coincident
(VGSI Angle 3.00/TCH 27).

IPREZ
3100

IGIDY
3300

4 NM Holding Pattern

112° → 3300
← 292°

GP 3.00°
TCH 40

RW29
3600 x 60

292° to RW29

CATEGORY	A	B	C	D
LNAV/VNAV DA	2119-1¾ 512 (600-1¾)			NA
LNAV MDA	2100-1	493 (500-1)	2100-1¼ 493 (500-1¼)	NA
CIRCLING	2120-1	513 (600-1)	2300-2 693 (700-2)	NA