

WAAS CH 69608 W36A	APP CRS 359°	Rwy Idg 6500 TDZE -2 Apt Elev 0
--	------------------------	--

RNAV (GPS) RWY 36

SOUTH LAFOURCHE LEONARD MILLER JR (G.A.O)



RNP APCH.

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -15°C or above 54°C. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM and LNAV Cat C and D visibility to 1 SM. When local altimeter setting not received, use Louis Armstrong New Orleans Intl altimeter setting and increase LPV DA to 275 feet, LNAV/VNAV DA to 325 feet and all MDA 80 feet and increase LNAV/VNAV all Cats visibility ½ SM, LNAV Cat C and D visibility ½ SM and Circling Cat C and D visibility ½ SM. For inop ALS, when using Louis Armstrong New Orleans Intl altimeter setting, increase LPV and LNAV/VNAV all Cats visibility ¾ SM. Baro-VNAV and VDP NA when using Louis Armstrong New Orleans Intl altimeter setting.

SSALR

MISSED APPROACH: Climb to 2000 direct HIKEN and hold.

AWOS-3PT 118.175	NEW ORLEANS APP CON 120.85 256.9	CLNC DEL 120.85	UNICOM 123.0 (CTAF)
----------------------------	--	---------------------------	-------------------------------



2000	HIKEN	JELON 1.8 NM to RW36	JOXAG	COPUP	4 NM Holding Pattern
*LNAV only.		*0.9 NM to RW36			
		RW36	1700	1700	2000
		0.9	0.9 NM	3.4 NM	6 NM
			620*		
			359°	179°	359°
					GP 3.00° TCH 51
CATEGORY	A	B	C	D	
LPV DA	198-½	200 (200-½)			
LNAV/VNAV DA	248-½	250 (300-½)			
LNAV MDA	340-½	342 (400-½)	340-⅝	342 (400-⅝)	
CIRCLING	440-1 440 (500-1)	560-1 560 (600-1)	640-1¾ 640 (700-1¾)	640-2 640 (700-2)	