

WAAS CH 50515 W32A	APP CRS 313°	Rwy ldg TDZE Apt Elev	3600 1608 1608
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 32


ROBERTSON FLD (D55)

RNP APCH - GPS.

Circling NA to Rws 8 and 26. Rwy 32 helicopter visibility reduction below ¾ SM NA. Baro-VNAV NA when using Devils Lake altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. When local altimeter setting not received, use Devils Lake altimeter setting and increase LPV DA to 1983 feet; increase LNAV/VNAV DA to 2284 feet and all visibilities ¼ SM. Increase all MDAs 140 feet and LNAV visibility Cat A/C ½ SM, and Circling visibility Cat A/C ½ SM.

MISSED APPROACH: Climb to 4000 direct MEKSE and on 223° track to JAKTI and on 132° track to CIDVA and hold.

AWOS-3 118.225	MINNEAPOLIS CENTER 132.15 269.6	UNICOM 122.8 (CTAF) 0
--------------------------	---	---------------------------------



4000

↑

MEKSE

✳

tr 223°

✳

JAKTI

✳

tr 132°

✳

CIDVA

✳

VGSI and RNAV glidepath not coincident

(VGSI Angle 3.00/TCH 27).

EHLEL

3500

313°

3500

133°

6000

4000

GP 3.00°

TCH 40

5.7 NM

6.1 NM

HA VIR

4 NM Holding Pattern

RW32

CATEGORY	A	B	C	D
LPV DA	1858-1 250 (300-1)			NA
LNAV/VNAV DA	2159-1½ 551 (600-1½)			NA
LNAV MDA	2360-1 752 (800-1)	2360-1¼ 752 (800-1¼)	2360-2 752 (800-2)	NA
CIRCLING	2360-1 752 (800-1)	2360-1¼ 752 (800-1¼)	2360-2¼ 752 (800-2¼)	NA

