


WAAS CH 45814 W16A	APP CRS 165°	Rwy Idg TDZE 3086 Apt Elev 3086
--	------------------------	---

RNAV (GPS) RWY 16

RONAN (7S)

RNP APCH.	NA Baro-VNAV NA when using Missoula altimeter setting. For uncompensated Baro-VNAV systems, procedure NA below -21°C or above 54°C. Circling NA east of Rwy 16-34. When local altimeter setting not received, use Missoula altimeter setting: increase LPV DA to 3550 and LNAV/VNAV DA to 3639 and all visibilities ¼ SM; increase all MDAs 120 feet and LNAV Cat B and Circling Cats A and B visibility ¼ SM.	MISSED APPROACH: Climb to 13000 direct IBBOR and on track 255° to HANIM and hold, continue climb-in-hold to 13000.
-----------	---	---

AWOS-3 119.925	SALT LAKE CITY CENTER 127.075 244.875	AUNICOM 122.8 (CTAF)
--------------------------	---	--------------------------------



VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 21).				
EGOCY	FATMI		IBBOR	HANIM
6700	5600		13000	
GP 3.00° TCH 40	5600		GEDKE 4 NM to RW16	
	*4400		tr 255°	
	6.7 NM			
	3.8 NM			
	4 NM			
CATEGORY	A	B	C	D
LPV DA	3443-1¼	357 (400-1¼)	NA	
LNAV/VNAV DA	3532-1⅜	446 (500-1⅜)	NA	
LNAV MDA	3800-1	714 (800-1)	NA	
CIRCLING	3800-1	714 (800-1)	NA	

