

WAAS CH 53341 W13A	APP CRS 133°	Rwy Ldg TDZE Apt Elev	3800 1879 1885
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 13

ONIDA MUNI (98D)

NA

DME/DME RNP-0.3 NA. VDP NA when using Pierre altimeter setting.
When local altimeter setting not received, use Pierre altimeter setting:
increase all MDAs 80 feet and Circling Cat C visibility ¼ SM.

MISSED APPROACH: Climb to 4200
direct XUSDY and hold.

AWOS-3P 120.0	MINNEAPOLIS CENTER 125.1 269.1	CTAF 122.9 0
-------------------------	--	------------------------

4 NM

133°

313°

(IF/IAF) WUKVA

3000

133°

(FAF) ZENEV

1902

ZIMAP 2.5 NM to RW13

1887±

1901

RW13

30 NM to WUKVA (NoPT)

4100

WUKVA

223°

043°

043°

4100

WUKVA

30 NM to WUKVA

MISSED APCH FIX

XUSDY

133°

313°

4 NM

ELEV 1885

TDZE 1879

4 NM Holding Pattern

WUKVA

4100

313°

133°

133°

ZENEV

3500

3.00°

TCH 40

ZIMAP 2.5 NM to RW13

2680

0.8 NM to RW13

RW13

6 NM

2.5 NM

1.7 NM

0.8

4200

XUSDY

133°

313°

0.6% UP

3800 X 60

2160 X 120

0.3% UP

31

MIRL Rwy 13-31 0

CATEGORY	A	B	C	D
LP MDA	2140-1	261 (300-1)		NA
LNAV MDA	2160-1	281 (300-1)		NA
CIRCLING	2400-1	515 (600-1)	2520-1¾ 635 (700-1¾)	NA

ONIDA, SOUTH DAKOTA

Orig 01FEB18

44°42'N-100°06'W

ONIDA MUNI (98D)

RNAV (GPS) RWY 13

NC-1, 30 OCT 2025 to 27 NOV 2025

NC-1, 30 OCT 2025 to 27 NOV 2025