

WAAS CH 56529 W07A	APP CRS 067°	Rwy Idg TDZE 3490 Apt Elev 3490
--	------------------------	---

RNAV (GPS) RWY 7

ROUNDUP (RPX)

NA

Use Billings altimeter setting, when not received, procedure NA.
When VGSi inop, Straight-in/Circling Rwy 7 procedure NA at night.
DME/DME RNP-0.3 NA. Visibility reduction by helicopters NA.

MISSED APPROACH: Climb to 6300 direct PULAE and hold.

BIL ASOS 126.3	SALT LAKE CENTER 126.85 305.2	UNICOM 122.8 (CTAF)	122.7
--------------------------	---	-------------------------------	--------------

		ELEV 3490		TDZE 3490	
7 NM Holding Pattern		VGSI and descent angles not coincident (VGSI Angle 4.00/TCH 43).		6300 PULAE	
6600		5200		4320	
7.5 NM		2.7 NM		2.5 NM	
CATEGORY	A	B	C	D	
LP MDA	3940-1	450 (500-1)	3940-1 3/8	450 (500-1 3/8)	
LNAV MDA	3960-1	470 (500-1)	3960-1 3/8	470 (500-1 3/8)	
CIRCLING	4000-1	510 (600-1)	4140-1 3/4	4340-2 3/4	850 (900-2 3/4)

MIRL Rwy 7-25

ROUNDUP, MONTANA
Orig-B 14JUL22

46°29'N-108°33'W

ROUNDUP (RPX)

RNAV (GPS) RWY 7

NW-1, 30 OCT 2025 to 27 NOV 2025

NW-1, 30 OCT 2025 to 27 NOV 2025