


WAAS CH 93518 W16A	APP CRS 164°	Rwy Idg TDZE 2433 Apt Elev 2437
--	------------------------	---

RNAV (GPS) RWY 16
MADRAS MUNI (S33)

NA -20°C	Baro-VNAV NA when using Redmond altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -19°C (-2°F) or above 54°C (130°F). Rwy 16 helicopter visibility reduction below ¾ SM NA. DME/DME RNP-0.3 NA. When local altimeter setting not received, use Redmond altimeter setting and increase all DA and MDA 580 feet; increase LPV all Cats visibility 2½ SM, LNAV/VNAV all Cats visibility 2½ SM, LNAV and Circling Cat A visibility ¼ SM, LNAV and Circling Cat B visibility ½ SM, and increase LNAV and Circling Cat C visibility ¼ SM.	MISSED APPROACH: Climb to 7000 direct HUKRI and on track 074° to JOREM and on track 042° to ZEMAB and hold.
----------------------------	---	---

AWOS-3PT 132.425	SEATTLE CENTER 126.15 269.475	UNICOM 122.8 (CTAF)
----------------------------	---	-------------------------------



	ELEV 2437		TDZE 2433	
	164°		164°	
	HETIM		HUKRI	
	5500		tr 074°	
	TIWEP		JOREM	
	4600		tr 042°	
	KIKCE		ZEMAB	
	4000		△	
	FEPOS 3.2 NM to RW16			
	*3500			
	RW16			
	* LNAV only			
	3.8 NM		2.4 NM	
	1.6 NM		3.2 NM	
CATEGORY	A	B	C	D
LPV DA	2783-1½	350 (400-1½)		NA
LNAV/VNAV DA	2843-1¾	410 (500-1¾)		NA
LNAV MDA	3040-1	607 (700-1)	3040-1¾ 607 (700-1¾)	NA
CIRCLING	3040-1	603 (700-1)	3040-1¾ 603 (700-1¾)	NA

