

WAAS
CH **48814**
W09A

APP CRS
091°

Rwy Idg **3401**
TDZE **244**
Apt Elev **244**

RNAV (GPS) RWY 9
CHUATHBALUK (9A3) (PACH)

NA

-31°C

Circling NA north of Rwy 9-27. DME/DME RNP- 0.3 NA. Visibility reduction by helicopters NA. Use Aniak altimeter setting; when not received, use Kalskag altimeter setting and increase all DA 58 feet and MDA 60 feet and increase LPV all Cats visibility ¼ mile, and increase LNAV and circling Cat C visibility ¼ mile.

MISSED APPROACH: Climb to 3400 direct PAWLA and hold.

ANCHORAGE CENTER
118.15 251.05

CTAF
122.9

The chart displays the RNAV (GPS) RWY 9 approach for Chuathbaluk, Alaska. Key features include:

- Approach Paths:** A series of waypoints including KOWWY, HINSU, FALUD, and REDOY, connected by a 091° heading. A 3200 NoPT altitude is specified for the initial segment.
- Altitudes:** Minimum altitudes of 3200, 3400, and 3600 feet are indicated at various points along the approach.
- Distances:** Distances of 4 NM, 6 NM, and 10 NM are marked between waypoints.
- Obstacles:** Obstacles are shown with their MSL altitudes, including 1000, 2000, 3366, and 864± feet.
- Navigation Aids:** The chart includes a compass rose showing the 091° heading and a scale of 1:100,000.

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 26).

3400 PAWLA

GP 3.00° TCH 40

6.1 NM 5.3 NM

CATEGORY	A	B	C	D
LPV DA	652-1½ 408 (500-1½)			NA
LNAV MDA	1000-1 756 (800-1)	1000-1¼ 756 (800-1¼)	1000-2¼ 756 (800-2¼)	NA
CIRCLING	1000-1 756 (800-1)	1000-1¼ 756 (800-1¼)	1000-2¼ 756 (800-2¼)	NA

MIRL Rwy 9-27

REIL Rws 9 and 27

CHUATHBALUK, ALASKA
Orig 22OCT09

61°35'N-159°13'W

CHUATHBALUK (9A3) (PACH)
RNAV (GPS) RWY 9