

WAAS CH 93742 W35A	APP CRS 353°	Rwy Ldg TDZE Apt Elev	5500 1409 1409
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 35
SIOUX COUNTY RGNL (SXX)

RNP APCH - GPS. Baro-VNAV and VDP NA when using LRJ altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. When local altimeter setting not received, use LRJ altimeter setting: increase LPV DA to 1668 feet; increase LNAV/VNAV DA to 1718 feet; increase all MDAs 60 feet and LNAV visibility Cat C/D ½ SM. For inop ALS, increase LNAV/VNAV all Cats visibility to ¾ SM, and LNAV Cat C/D visibility to ¾ SM. For inop ALS when using LRJ altimeter setting, increase LNAV/VNAV all Cats visibility to ¾ SM, and LNAV Cat C/D visibility to 1 SM.	MALSR 45 MISSED APPROACH: Climb to 4500 direct HALGA and hold, continue climb-in-hold to 4500.
---	--

AWOS-3P 120.075	SIOUX CITY APP CON ★ 124.6 307.0	UNICOM 122.7 (CTAF)
---------------------------	--	-------------------------------

