

ILS or LOC RWY 23

LOC I-POB <u>110.9</u>	APCH CRS <u>228°</u>	Rwy Idg TDZE 7501 <u>200</u> Arprt Elev <u>225</u>	[USAF]
----------------------------------	--------------------------------	---	--------

POPE AAF (KPOB)

RADAR required

- * When ALS inop, increase RVR to 40 and vis to ¾ mile.
- ** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile; CAT CD RVR to 60, vis to 1½ miles.
- *** Circling not authorized SE of Rwy 5-23.
- **** When ALS inop, increase CAT AB RVR to 55 and vis to 1 mile; CAT CD vis to 1½ miles.

ALS-1

ATIS	FAYETTEVILLE APP CON	TOWER	GND CON	CLNC DEL
132.3 353.725	125.175 285.575 (271° - 090°) 133.0 290.25 (091° - 270°)	135.025 291.1	124.55 275.8	124.55 275.8

ELEV 225	D	TDZE 200
-----------------	----------	-----------------

CATEGORY	A	B	C	D
S-ILS 23 *	400/24		200 (200-½)	
S-LOC 23 **	620/24	420 (500-½)	620/40	420 (500-¾)
CIRCLING ***	760-1	542 (600-1)	920-2 702 (800-2)	1060-2 ¾ 842 (900-2 ¾)

WITHOUT LAST STEPDOWN FIX

S-LOC 23 ****	640/24	440 (500-½)	640/45	440 (500-¾)
---------------	--------	-------------	--------	-------------

HRL Rwy 05-23
LIRL Rwy 05R-23L
REIL Rwy 05

FAF to MAP 3.2 NM

Knots	60	90	120	150	180
Min:Sec	3:12	2:08	1:36	1:17	1:01

SE-2, 27 NOV 2025 to 25 DEC 2025

SE-2, 27 NOV 2025 to 25 DEC 2025