

LOC I-POU 111.3	APP CRS 063°	Rwy Ldg TDZE 156 Apt Elev 164
---------------------------	------------------------	---

ILS or LOC RWY 6
HUDSON VALLEY RGNL (POU)

DME required for LOC only.



⚠ Circling NA to Rwys 7 and 25. Circling Rwy 15, 33 NA at night. Rwy 6 helicopter visibility reduction below $\frac{3}{4}$ SM NA. DME from IGN VOR/DME. Simultaneous reception of I-POU and IGN DME required. For inop ALS, increase S-LOC 6 Cats C/D visibility to $1\frac{1}{2}$ SM. When local altimeter setting not received, use Montgomery altimeter setting: increase S-ILS 6 DA to 556; increase all MDA 80 feet and S-LOC 6 and Circling Cats C/D visibility $\frac{1}{4}$ SM. Inop table does not apply to S-ILS 6 all Cats and S-LOC 6 Cats A/B. For inop ALS when using Montgomery altimeter setting, increase S-ILS 6 all Cats visibility to $1\frac{1}{2}$ SM and S-LOC 6 Cats C/D visibility to $1\frac{1}{2}$ SM.

MALSR



MISSED APPROACH:
Climb to 3000 direct
IGN VOR/DME and
hold, continue
climb-in-hold
to 3000.

ATIS 126.75	NEW YORK APP CON 132.75 363.1	DUTCHESS COUNTY TOWER ★ 124.0 (CTAF) 0 269.15	GND CON 121.8	UNICOM 122.95
-----------------------	---	--	-------------------------	-------------------------



CATEGORY	A	B	C	D
S-ILS 6		485-1	329 (400-1)	
S-LOC 6		640-1	484 (500-1)	
CIRCLING	760-1 596 (600-1)	840-1 676 (700-1)	940-2 $\frac{1}{4}$ 776 (800-2 $\frac{1}{4}$)	1080-3 916 (1000-3)

