

LOC/DME I-JAC
109.1
Chan **28**

APP CRS
187°

Rwy Ldg
TDZE **6451**
Apt Elev **6451**

ILS Z or LOC Z RWY 19
JACKSON HOLE (JAC)

DME required for LOC only. RNAV 1-GPS required. RADAR required for procedure entry at MOSSS.

▼

▲

❄

Circling NA for Cats A, B, and C east of Rwy 1-19. Inop table does not apply to S-ILS 19*. Circling NA for Cat D. For inop ALS increase S-LOC 19# Cats C and D visibility to RVR 4500.

MALS

A4

MISSED APPROACH: Climb to 6900 then climbing right turn to 14000 on JAC VOR/DME R-192 to KICNE INT/JAC 26.6 DME and hold, continue climb-in-hold to 14000.

*Missed approach requires minimum climb of 225 feet per NM to 9400; if unable to meet climb gradient, see ILS Y or LOC Y RWY 19.

#Missed approach requires minimum climb of 234 feet per NM to 9600; if unable to meet climb gradient, see ILS Y or LOC Y RWY 19.

D-ATIS 120.625	SALT LAKE CENTER 133.25 285.6	JACKSON TOWER* 118.075 (CTAF)	GND CON 124.55	UNICOM 122.95
--------------------------	---	---	--------------------------	-------------------------

6900

14000

KICNE

VGSI and ILS glidepath not coincident (VGSI Angle 3.00/TCH 53).

ZOSUV

ZIBIV

I-JAC

I-JAC

SOSUE

1.2

1.9

4.5

7540

8000

8700

9800

11000

0.7

2.6 NM

1.4 NM

2.7 NM

4 NM

4.3 NM

CATEGORY

A

B

C

D

S-ILS 19*

6651/40

200 (200-¾)

S-LOC 19#

6720/40

269 (300-¾)

CIRCLING

6840-1
389 (400-1)

6960-1
509 (600-1)

7440-3
989 (1000-3)

NA

Use I-JAC DME when on the localizer course.

TWR

CL Rwy 1-19

HIRL Rwy 1-19

JACKSON, WYOMING

Amtd 2 20APR23

43°36'N-110°44'W

JACKSON HOLE (JAC)

ILS Z or LOC Z RWY 19