

SPRINGFIELD, MISSOURI

HI-TACAN RWY 20

VORTAC SGF
116.9
Chan **116**

APCH CRS
196°

Rwy Idg **7003**
TDZE **1262**
Arpt Elev **1268**

AL-604 [USAF]

SPRINGFIELD-BRANSON NATL (KSGF)

When local altimeter setting not received, use Monett altimeter setting.

MALS

MISSED APPROACH: Climb to 3000 then right turn via SGF VORTAC R-206 to BLUE INT/SGF 22 DME and hold.

ATIS
135.125

APP CON
121.1 290.5

TOWER
119.9 257.8

GND CON
121.9 251.15

CLNC DEL
123.675

SPRINGFIELD
116.9 SGF
Chan 116

DOGWOOD
109.4 DGD
Chan 31

EMERG SAFE ALT 100 NM 4600

3000

BLUE SGF 22

VDP NA when using Monett altimeter setting.

VORTAC

FEBKI 7

POTHE 22

15,000

3.02°

TCH 47

6.5 NM

CATEGORY	C	D	E
S-20	1760-1¼ 498 (500-1¼)	1760-1½ 498 (500-1½)	1760-1¾ 498 (500-1¾)
CIRCLING	1820-1½ 552 (600-1½)	1820-2 552 (600-2)	1920-2¼ 652 (700-2¼)

MONETT ALTIMETER SETTING MINIMUMS

S-20	1860-1½ 598 (600-1½)	1860-1¾ 598 (600-1¾)	1860-2 598 (600-2)
CIRCLING	1920-1¾ 652 (700-1¾)	1920-2¾ 652 (700-2¾)	2020-2¾ 752 (800-2¾)

ELEV 1268

TDZE 1262

196° 6.5 NM from VORTAC

1309

8000 X 150

TWR 1361

REIL Rwy 32

HIRL Rwy 2-20 and 14-32

HI-TACAN RWY 20

NC-3, 27 NOV 2025 to 25 DEC 2025

NC-3, 27 NOV 2025 to 25 DEC 2025