

|                                        |                        |                                                   |
|----------------------------------------|------------------------|---------------------------------------------------|
| WAAS<br>CH <b>53537</b><br><b>W21A</b> | APP CRS<br><b>205°</b> | Rwy Ldg<br>TDZE <b>935</b><br>Apt Elev <b>937</b> |
|----------------------------------------|------------------------|---------------------------------------------------|

RNAV (GPS) RWY 21  
DELAWARE COUNTY RGNL (MIE)

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C (-4°F) or above 54°C (130°F). DME/DME RNP-0.3 NA. When local altimeter setting not received, use Fort Wayne Intl altimeter setting and increase all DA 121 feet and all MDA 140 feet; increase LPV all Cats and LNAV Cats C/D visibility ¾ mile and LNAV/VNAV all Cats and Circling Cats C/D visibility ½ mile. Baro-VNAV and VDP NA when using Fort Wayne Intl altimeter setting. Helicopter visibility reduction below ¾ SM NA.

MISSED APPROACH:  
Climb to 2800 direct  
APPAL and hold.

|                       |                                             |                                         |                         |                         |
|-----------------------|---------------------------------------------|-----------------------------------------|-------------------------|-------------------------|
| ATIS<br><b>133.25</b> | INDIANAPOLIS APP CON<br><b>120.65 317.8</b> | MUNCIE TOWER ★<br><b>120.1 (CTAF) 0</b> | GND CON<br><b>121.9</b> | UNICOM<br><b>122.95</b> |
|-----------------------|---------------------------------------------|-----------------------------------------|-------------------------|-------------------------|

