


WAAS CH 90339 W21A	APP CRS 213°	Rwy ldg TDZE 170 Apt Elev 170
--	------------------------	---

RNAV (GPS) RWY 21
SANTA MONICA MUNI (SMO)

RNP APCH. ▼ For uncompensated Baro-VNAV systems, LNAV/VNAV NA below 5°C (41°F) or above 14°C (58°F). Rwy 21 helicopter visibility reduction below 1 SM NA. ▲	MISSED APPROACH: Climb to 600 then climbing right turn to 5000 direct CAPOB and on track 283° to SADDE and hold, continue climb-in-hold to 5000.
--	--

ATIS 119.15	SOCAL APP CON 135.05 317.5	SANTA MONICA TOWER * 120.1 (CTAF) 257.8	GND CON 121.9	UNICOM 122.95
-----------------------	--------------------------------------	---	-------------------------	-------------------------



RADAR REQUIRED

600	5000	CAPOB	tr 283°	SADDE	VGSI and RNAV glidepath not coincident (VGSI Angle 3.50/TCH 45).
↑	↘	✱		△	

* LNAV only

MIPT 3.3 NM to RW21

* 2.4 NM to RW21

MOVE 3000

DARTS 4200

213°

219°

3000

1440*

GP 3.50° TCH 53

2.4 NM 0.9 NM 4.2 NM 4.6 NM

CATEGORY	A	B	C	D
LPV DA	440-1 270 (300-1)			
LNAV/VNAV DA	685-1 515 (600-1)			
LNAV MDA	1120-1 950 (1000-1)		1120-2 950 (1000-2)	

ELEV 170	TDZE 170
----------	----------