

LOC/DME I-GFK 109.1 Chan 28	APP CRS 174°	Rwy Ldg TDZE 843 Apt Elev 845
---	------------------------	---

LOC BC RWY 17R


GRAND FORKS INTL (GFK)

DME or ADF or RADAR required.


▼ When local altimeter setting not received, use Crookston altimeter setting and increase all MDA 80 feet; increase S-17R Cat C visibility ¼ SM and Circling Cat C visibility ¼ SM. Increase WUSIK fix minimums S-17R Cat C visibility and Circling Cat C visibility ¼ SM.

MISSED APPROACH: Climb to 2600 on I-GFK south course (174°) to HISER LOM/I-GFK 6.9 DME/RADAR and hold.

ATIS 119.4	GRAND FORKS APP CON ★ 118.1 318.1	GRAND FORKS TOWER ★ 118.4 (CTAF) 350.35	GND CON 124.575	CLNC DEL 135.725	UNICOM 122.95
----------------------	---	---	---------------------------	----------------------------	-------------------------



ELEV 845	D	TDZE 843
-----------------	----------	-----------------




MIRL Rwy 9L-27R, 9R-27L and 17L-35R

HIRL Rwy 17R-35L

REIL Rwy 17R, 9L, and 27R

FAF to MAP 4.4 NM					
Knots	60	90	120	150	180
Min:Sec	4:24	2:56	2:12	1:46	1:28



CATEGORY	A	B	C	D
S-17R	1300-1	457 (500-1)	1300-1⅓ 457 (500-1⅓)	1300-1½ 457 (500-1½)
CIRCLING	1300-1	455 (500-1)	1400-1½ 555 (600-1½)	1420-2 575 (600-2)
WUSIK FIX MINIMUMS				
S-17R	1200-1 357 (400-1)			1200-1¼ 357 (400-1¼)
CIRCLING	1260-1 415 (500-1)	1300-1 455 (500-1)	1400-1½ 555 (500-1½)	1420-2 575 (600-2)