

OZARK EIGHT DEPARTURE

AL-5316 (FAA)

ST LOUIS DOWNTOWN (CPS)
CAHOKIA/ST. LOUIS, ILLINOIS

EC-3, 27 NOV 2025 to 25 DEC 2025

ATIS
121.45
CLNC DEL
118.275
121.8 (when tower closed)
GND CON
121.8
DOWNTOWN TOWER*
119.925 379.3
ST LOUIS DEP CON
123.7 371.875



HAILLSVILLE
114.2 HLY
Chan 89

8000
*2500
281°
(46)

V4

R-095

CABIT

8000
*2100
281°
(32)


NOTE: DME and RADAR required.

ST. LOUIS
117.4 STL
Chan 121

V4

TAKEOFF MINIMUMS

Rwys 12L/R, 23, 30R: Standard.
Rwy 5: 200-1¼ or standard with minimum climb of 343' per NM to 700.
Rwy 30L: 400-2½ or standard with minimum climb of 220' per NM to 900, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 2100' prior to DER.



(CONTINUED ON FOLLOWING PAGE)

NOTE: Chart not to scale.

OZARK EIGHT DEPARTURE

EC-3, 27 NOV 2025 to 25 DEC 2025