

WAAS
CH **63014**
W29A

APP CRS
290°

Rwy Idg
TDZE
Apt Elev

5101
1724
1730

RNAV (GPS) RWY 29

SCHUYLKILL COUNTY/JOE ZERBEY (ZÉR)

RNP APCH - GPS

▼

▲ NA


Circling NA to Rwys 4 and 22. Baro-VNAV NA when using Selinsgrove altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -18°C or above 54°C. VDP NA when using Selinsgrove altimeter setting. When local altimeter setting not received, use Selinsgrove altimeter setting: increase LPV DA to 2156 feet and visibility ½ SM; LNAV/VNAV DA to 2376 feet and visibility ¾ SM; increase all MDAs 240 feet and visibility LNAV Cats C/D ⅝ SM and Circling Cats C/D ½ SM.

MISSED APPROACH:
Climb to 4000 direct
IRCIT and hold.

AWOS-3
127.575

HARRISBURG APP CON
118.25 269.45

UNICOM
123.075 (CTAF) 0



ELEV 1730

TDZE 1724

4000

IRCIT

REIL Rws 11 and 29

MIRL Rwy 11-29

1.2 NM to RW29

1.2 NM

3.7 NM

6.1 NM

3300

3300

3300

3300

290°

290°

290°

290°

110°

110°

110°

110°

4 NM

4 NM

4 NM

4 NM

6000

6000

6000

6000

4100

4100

4100

4100

GP 3.00°

GP 3.00°

GP 3.00°

GP 3.00°

TCH 45

TCH 45

TCH 45

TCH 45

CATEGORY	A	B	C	D
LPV DA	1924-¾	200 (200-¾)		
LNAV/VNAV DA	2144-1⅛	420 (500-1⅛)		
LNAV MDA	2120-1	396 (400-1)	2120-1⅛	396 (400-1⅛)
CIRCLING	2160-1 430 (500-1)	2180-1 450 (500-1)	2180-1½ 450 (500-1½)	2280-2 550 (600-2)