

WAAS CH 53701 W06A	APP CRS 059°	Rwy Ldg 5500 TDZE 547 Apt Elev 547
--	------------------------	---


RNAV (GPS) RWY 6
MUSCATINE MUNI (MUT)

RNP APCH - GPS.


T Rwy 6 helicopter visibility reduction below $\frac{3}{4}$ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -16°C or above 54°C. If local altimeter setting not received, use Iowa City Muni altimeter setting and increase all DAs/MDAs 80 feet. Baro-VNAV and VDP NA when using lowa City Muni altimeter setting.

MISSED APPROACH: Climb to 3000 direct EDAGE and hold.

AWOS-3P 120.625	QUAD CITY APP CON ★ 133.275 257.8	CLNC DEL 119.125	UNICOM 122.7 (CTAF) 0
---------------------------	---	----------------------------	---------------------------------



ELEV	547		TDZE	547
------	-----	--	------	-----



CATEGORY	A	B	C	D
LPV DA	1076-2 529 (600-2)			
RNAV/ VNAV DA	1232-2 685 (700-2)			1232-2¼ 685 (700-2¼)
RNAV MDA	1120-1 573 (600-1)		1120-1½ 573 (600-1½)	1120-1¾ 573 (600-1¾)
CIRCLING	1120-2½ 573 (600-2½)	1200-2½ 653 (700-2½)		1500-3 953 (1000-3)