

WAA5	APP CRS	Rwy ldg	3700
CH 69536	218°	TDZE	354
W22A		Apt Elev	354

RNAV (GPS) RWY 22

WASILLA (IYS) (PAWS)

RNP APCH.


▼

⚠

Circling NA to Rwy 4S and 22S. Baro-VNAV and VDP NA when using Palmer altimeter setting. Rwy 22 helicopter visibility reduction below 3/4 SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -25°C or above 54°C. When local altimeter setting not received, use Palmer altimeter setting and increase all DA 46 feet, MDA 60 feet and all visibilities 1/8 mile.

MISSED APPROACH:
Climb to 1000 then
climbing right turn to
3000 direct BGQ
VORTAC and hold.

AWOS-3P 135.25	ANCHORAGE APP CON 119.1 363.2	CTAF 122.8 0
-------------------	----------------------------------	-----------------



ELEV 354 TDZE 354

1000 3000 BGQ

↑

↷

⬢

*LNAV only

ODUWU 1.9 NM to RW22

*1.2 NM to RW22

WOKNA 2500

RW22 218°

2500

227°

4400

JODBI

GP 3.31° TCH 40

1060*

1.2 NM 0.7 NM 4.1 NM 6 NM

CATEGORY	A	B	C	D
LPV DA	604-3/4	250 (300-3/4)	NA	
LNAV/VNAV DA	821-1 1/2	467 (500-1 1/2)	NA	
LNAV MDA	800-1	446 (500-1)	NA	
CIRCLING	1000-1	646 (700-1)	NA	