

WAAS
CH **77504**
W17A

APP CRS
172°

Rwy Ldg
TDZE **146**
Apt Elev **146**

RNAV (GPS) RWY 17

AUGUSTA RGNL AT BUSH FLD (AGS)

RNP APCH - GPS.

▼

▲

For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -6°C or above 54°C.

For inop ALS, increase LNAV/VNAV all Cats visibility to RVR 4500.

MALS

MISSED APPROACH:
Climb to 2100 direct
HOMRU and hold.

ATIS 132.75	AUGUSTA APP CON★ 126.8 270.3	AUGUSTA TOWER★ 118.7 (CTAF) 239.3	GND CON 121.9 348.6	UNICOM 122.95
-----------------------	--	---	-------------------------------	-------------------------

The main chart illustrates the RNAV (GPS) RWY 17 approach. It begins at a 30 NM distance from WASAP (IAF) at 3000 feet, heading 082°. The path continues to WASAP (IAF) at 3000 feet, then to CARD0 (IF/IAF) at 2400 feet NoPT, heading 262°. From CARD0, the path splits: one branch goes to HOGEM (FAF) at 1800 feet, heading 172°, and then to RW17 at 146 feet. The other branch goes to POGEE (IAF) at 2400 feet NoPT, heading 262°, and then to POGEE at 3000 feet, heading 352°. A missed approach fix (HOMRU) is shown at 2100 feet, heading 172°. The chart also includes a 4 NM holding pattern at CARD0 and a 30 NM to WASAP arc.

4 NM Holding Pattern

VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 71).

2100 HOMRU

6000 ← 352°

2400 ← 172°

GP 3.00° TCH 57

1800

1800

1.5 NM to RW17

6.9 NM

3.5 NM

1.5 NM

CATEGORY	A	B	C	D
LPV DA		351/24	205 (300-½)	
LNAV/VNAV DA		460/24	314 (400-½)	
LNAV MDA	700/24	554 (600-½)	700/60	554 (600-1¼)
CIRCLING	780-1	634 (700-1)	780-1¾ 634 (700-1¾)	940-2½ 794 (800-2½)

ELEV 146

TDZE 146

172°

4

8001 X 150

TWR

8

6002 X 75

35

MIRL Rwy 8-26
HIRL Rwy 17-35
REIL Rwy 8 and 26

AUGUSTA, GEORGIA
Amdt 3A 29DEC22

33°22'N-81°58'W

AUGUSTA RGNL AT BUSH FLD (AGS)
RNAV (GPS) RWY 17