

ILS or LOC RWY 3

LOC I-COF

109.1

APCH CRS

027°

Rwy Idg

9008

TDZE

5

Arpt Elev

8

[USAF]

PATRICK SFB

(KCOF)

DME required

▼ * When ALS inop, increase RVR to 40 and vis to ¾ mile.

** When ALS inop, increase CAT AB RVR to 55, vis to 1 mile; CAT CD vis to 1½ miles.

*** Circling not authorized NW of Rwy 3-21. When Rwy 29 VGSi inop, circling to Rwy 29 NA at night. When circling to Rwy 29 at night, operational VGSi required, remain on or above VGSi glidepath until threshold.

ALSF-1

MISSED APPROACH: Climb to 600, then climbing right turn to 3000 and intercept COF TACAN R-110 direct ZEVEX/COF 12 DME and hold.

ATIS ★

119.175 273.5

ORLANDO APP CON ★

126.025 281.425

TOWER ★

133.75 269.375

GND CON ★

124.35 335.8

CLNC DEL ★

118.4 289.4

1046

▲

PATRICK

Chan 97 COF

(115.0)

LOCALIZER 109.1

I-COF

GEPRE COF

1.5

333

▲

26

▲

207

▲

241

▲

80

▲

124

▲

R-110

HOLD 8000

110°

290°

(IAF) ZEVEX COF 12

3000

MSA COF 2.5 NM

3000

1700

350°

278

▲

JAPEK COF 7.1

4.9

FIVMA RADAR COF

2000

027°

1300

207

▲

475

▲

(IF) FIGDA COF 12

525

R-207

LR-196

ELEV

8

D

TDZE

5

152

▲

109

▲

11

3993

× 200

200

TWR

166

▲

027°

HIRL Rwy 3-21

MIRL Rwy 11-29

FAF to MAP 3.4 NM

Knots

60

90

120

150

180

Min:Sec

3:24

2:16

1:42

1:22

1:08

EMERG SAFE ALT 100 NM 3000

600

3000

ZEVEX COF 12

3000

FIGDA Intep Lczz COF 12

3000

JAPEK COF 7.1

2000

FIVMA COF 4.9

1300

RADAR

1300

COF 2.3

1300

GEPRE COF 1.5

1300

Arc

12

GS 3.00°

TCH 51

3.4 NM

0.5

R-110

CATEGORY	A	B	C	D
S-ILS 3 *	205/24	200	(200-½)	
S-LOC 3 **	460/24	455 (500-½)	460/45	455 (500-¾)
CIRCLING ***	520-1	512 (600-1)	540-1½ 532 (600-½)	560-2 552 (600-2)

Cocoa Beach, Florida

28° 14' N - 80° 37' W

PATRICK SFB (KCOF)

ILS or LOC RWY 3

SE-3, 25 DEC 2025 to 22 JAN 2026

SE-3, 25 DEC 2025 to 22 JAN 2026