


WAAS CH 90105 W21A	APP CRS 206°	Rwy Idg TDZE Apt Elev	5465 1486 1503
--	------------------------	-----------------------------	---


RNAV (GPS) RWY 21

ALTOONA/BLAIR COUNTY (A00)

RNP APCH - GPS.		MALSR 	MISSED APPROACH: Climb to 5000 direct YOLUP and on track 223° to CRYSS and hold, continue climb-in-hold to 5000.
Circling NA to Rwys 12 and 30. Circling NA for Cats C, D northwest of Rwys 12 and 21. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -17°C or above 54°C. For inop ALS, increase LPV visibility all Cats to 1½ SM.			
ASOS 127.125	JOHNSTOWN APP CON ★ 121.2 299.2	CTAF 123.60	



ELEV 1503	D	TDZE 1486
-----------	----------	-----------



5000	YOLUP	CRYSS	ROBPO	KEWER	4 NM Holding Pattern
↑		tr 223°			
			ZAVMA 3 NM to RW21		
			2 NM to RW21		
			2460	3500	
			2 NM	1 NM	3.2 NM
					5.9 NM
CATEGORY	A	B	C	D	
LPV DA	1977-1	491 (500-1)			
INAV/VNAV DA	1999-1	513 (500-1)			
INAV MDA	2160-1/2	674 (700-1/2)	2160-1/2	674 (700-1/2)	
CIRCLING	2240-1	737 (800-1)	2800-3	2840-3	
			1297 (1300-3)	1337 (1400-3)	