

ILS or LOC RWY 24
ELMIRA/CORNING RGNL (ELM)

MISSED APPROACH:
Climb to 4000 direct
UNOLY/RADAR and hold.
** Missed approach
requires minimum
climb of 260 feet
per NM to 2400.



** S-ILS 24 RVR 1800 authorized with use of FD or AP or HUD to DA.

IAF
ALPINE
245 ALP :≡:..
RADAR

LOCALIZER 109.1
I-ELM :≡:..
1348±

ERINN RADAR

HOLD 5400
4000

4 NM

062°

242°

3200

242° (7.2)

(IF/IAF)
IREKE
RADAR

30 NM to IREKE (NoP)

152°

332°

4000

IREKE

30 NM to IREKE

152°

332°

4000

IREKE

MISSED APCH FIX
UNOLY
RADAR

062°

242°

4 NM

ELEV 955

D TDZE 955

4000
↑
UNOLY RADAR

* LOC only.

ERINN RADAR

ALP NDB RADAR

IREKE RADAR

4 NM Holding Pattern

3158

2060*

3200

062° → 5400

← 242° 4000

GS 3.00°
TCH 53

3.3 NM

3.5 NM

7.2 NM

CATEGORY	A	B	C	D
S-ILS 24**	1155/24		200 (200-½)	
S-ILS 24	1340/35		385 (400-¾)	
S-LOC 24	2060/40 1105 (1200-¾)	2060/55 1105 (1200-1)	2060-3	1105 (1200-3)
CIRCLING	2060-1¼ 1105 (1200-1¼)	2080-1½ 1125 (1200-1½)	2100-3 1145 (1200-3)	2340-3 1385 (1400-3)
ERINN FIX MINIMUMS				
S-LOC 24	1600/24	645 (700-½)	1600-1⅜	645 (700-1⅝)
CIRCLING	2020-1¼ 1065 (1100-1¼)	2080-1½ 1125 (1200-1½)	2100-3 1145 (1200-3)	2340-3 1385 (1400-3)