

WAAS CH 42827 W06A	APP CRS 062°	Rwy Ldg TDZE Apt Elev	7401 944 955
--	------------------------	-----------------------------	---

RNAV (GPS) RWY 6

ELMIRA/CORNING RGNL (ELM)

RNP APCH.

⚠

⚠

⚠

Inop table does not apply to LNAV/VNAV all Cats. Circling Rwy 10 NA at night. Circling NA to Rwys 5 and 23. Circling NA for Cat D south of Rwys 10 and 28. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -21°C or above 54°C. # RVR 1800 authorized with use of FD or AP or HUD to DA.

MALSR

MISSED APPROACH: Climb to 4000 direct IREKE and hold.

ATIS 125.475	ELMIRA APP CON ★ 128.425 257.8	ELMIRA TOWER ★ 121.1 (CTAF) 0 257.8	GND CON 121.9	CLNC DEL 121.9	UNICOM 122.95
------------------------	--	---	-------------------------	--------------------------	-------------------------

4 NM Holding Pattern		UNOLY	JOKEN	CONAC	IREKE
6000 ← 242°		062° →	3200	4.2 NM to RW06	↑
GP 3.00° TCH 52				* 3 NM to RW06	★
					* INAV only
		7 NM	2.8 NM	1.2 NM	3 NM
CATEGORY	A	B	C	D	
LPV DA #		1144/24	200 (200-½)		
LNAV/VNAV DA		2138-5	1194 (1200-5)		
LNAV MDA	1940/40 996 (1000-¾)	1940/55 996 (1000-1)	1940-2½	996 (1000-2½)	
CIRCLING	2020-1¼ 1065 (1100-1¼)	2080-1½ 1125 (1200-1½)	2100-3 1145 (1200-3)	2340-3 1385 (1400-3)	

ELEV 955 D TDZE 944

ELMIRA/CORNING, NEW YORK
Amdt 3 31DEC20

42°10'N-76°54'W

ELMIRA/CORNING RGNL (ELM)

RNAV (GPS) RWY 6